


Tê 90° com redução
 Te reducida 90°
 Té réduit 90°
 E-T-Stück 90° reduziert

Fabricado por molde
 Fabriqué par moulage

Fabricado mediante moldeo
 Produziert mit Spritzgußverfahren



PN16 SDR11



www.plastfast.eu

	dn	dn1	código	H [mm]	Z [mm]	Peso [Kg]
f	90	63	TREP090063C	65	209	0,92
f	90	75	TREP090075C	66	209	0,98
f	110	63	TREP110063C	66	250	1,48
f	125	63	TREP125063C	66	265	2,08
f	125	90	TREP125090C	82	265	2,18
f	140	110	TREP140110C	83	290	2,82
f	160	110	TREP160110C	88	318	4,17
f	180	90	TREP180090C	85	336	5,38
f	180	125	TREP180125C	93	336	5,48
f	200	90	TREP200090C	82	415	7,56
f	200	125	TREP200125C	88	415	7,73
f	200	180	TREP200180C	107	415	7,96
f	225	110	TREP225110C	90	415	10,00
f	225	160	TREP225160C	99	415	10,38
f	250	125	TREP250125C	93	478	14,95
f	250	180	TREP250180C	110	478	15,58
f	315	125	TREP315125C	93	560	25,72
f	315	180	TREP315180C	110	560	27,42